



SLIMBASS ANGLE®

TUNED ABSORPTION PANEL




Image of 120x30cm model Ref.:SLB120 (on the left) and Ref.:SLB120 applied (ambient image).

DESCRIPTION


Music rooms, studios, rehearsal rooms, etc., require a surface that is efficient at absorbing low-frequencies.

ATP® proposes the SLIMBASS ANGLE® absorbent panel for the absorption of low-frequencies.

It is made of high-quality controlled-cell self-extinguishable M1 fire retardant acoustic foam with a wooden-like synthetic PVC finish exclusive membrane. It forms inside it a 160 Hz closed resonance box.

The SLIMBASS ANGLE® panel has a thin and elegant design, which is appropriate for the 90° corners of the room's walls or ceilings.

TECHNICAL DRAWINGS




FEATURES

- Average absorption: 0.55/m² [$>100\text{Hz}; <250\text{Hz}$].
- Self-extinguishable M1 fire-retardant acoustic foam.
- Package: 4 units.
- Very easy to install.

MODELS AND SIZES

MODELS	HEIGHT	WIDTH	DEPTH	WEIGHT
SLB120	120 cm	30 cm	30 cm	1.4 Kg

ABSORPTION COEFFICIENT



■ ABSORPTION COEFFICIENT: Values in accordance with the standards: EN 20654, ASTM C423 and EN 11654.

■ Values [$<100\text{Hz}$ and $>5\text{K}$] are Non Standard Values.

MELAMIN FACED BOARD FINISHINGS



REGULAR FOAM COLOURS



IMPORTANT NOTICES

- JOCAVI® accepts no responsibility for any printing errors. Specifications can be modified without prior notice, if technical or commercial reasons so require.
- The colours shown on this catalogue are only a reference and an illustration of the products finishing. The colours shown are not binding because brightness, contrast and colour balance may vary due to the printing process.
- Colours may vary due to raw-material suppliers' changes and some differences may occur in tonal range.
- Due to its natural origin, wood-based products will always present natural imperfections inherent to the organic nature. And for similar reasons, they will also present traces of old-age in the course of time.
- Wood and Fabric products are highly susceptible to change its appearance with humidity and temperature. Close attention must be paid to the storage conditions and the acclimatization before, during and after the installation.
- Typical Indoor Comfort Standards state a temperature range of 20°C - 27°C (68°F - 81°F), and a relative humidity of less than 60%. These would be considered as normal operational levels of JOCAVI® products' range.
- Despite all the standard sizes of all products, this model can be customised upon previous consultation. Sizes may vary slightly due to their production method and some inherent raw-materials characteristics.

