



ws	: wit	blanc	weiss	white
br	: bruin	brun	braun	brown
gn	: groen	vert	grun	green
ge	: geel	jaune	gelb	yellow
gr	: grijs	gris	grau	grey
rs	: roos	rose	rosa	pink
bl	: blauw	bleu	blau	blue
rt	: rood	rouge	rot	red
sw	: zwart	noir	schwarz	black
vi	: paars	violet	violett	violet
be	: beige	beige	beige	tan
or	: oranje	orange	orange	orange

TOP VIEW CONNECTOR:		pair	color code	T568B	pin	T568B		
pair 3	pair 2	pair 1	pair 4	1	ws-bl	5	1	ws-or
				2	bl	4	2	or
3	4	5	6	3	ws-or	1	3	ws-gn
				4	or	2	4	bl
4	5	6	7	5	ws-gn	3	5	ws-bl
				6	gn	6	6	gn
7	8	1	2	7	ws-br	7	7	ws-br
				8	br	8	8	br

Terminal N°1 is the terminal to the extreme left as you face the cable opening, latch tab down.

Технические характеристики

Диаметр проводников	24AWG (7x0.20 ± 0.005мм) многожильный медный провод
Диаметр диэлектрика	0.95± 0.03мм
Кол-во витых пар	4
Соединитель	Модульный U.S. экранированный 10P10C
Материал кожуха	LSZH
Код продукта	71.60.4002 (2 метра) 71.60.4005 (5 метров) 71.60.4010 (10 метров) 71.60.4020 (20 метров)